Model	BASE	PLUS	BASE	PLUS	BASE	PLUS
Unit Length	36'	36'	40'	40'	44'	44'
Axle Rating (QTY) lbs/axle	(2) 7000#	(2) 7000#	(2) 7000#	(2) 7000#	(3) 7000#	(3) 7000#
GVWR (lbs)	16,100	16,100	16,100	16,100	24,150	24,150
Dry Weight (lbs)*	5,700	5,900	6,100	6,350	7,000	7,300
Payload (lbs)*	10,400	10,200	10,000	9,750	17,150	16,850
Axle Type	Torsion	Torsion	Torsion	Torsion	Torsion	Torsion
Overall Length	36'-9"	36'-9"	40'-9"	40'-9"	44'-9"	44'-9"
Overall Width	102"	102"	102"	102"	102"	102"
Overall Height **	10' 1-7/8	10' 1-7/8	10' 1-7/8	10' 1-7/8	10' 1-7/8	10' 1/4"
Interior Length Main Floor	27' 4"	27' 4"	31'-4"	31'-4"	35'-4"	35'-4"
Interior Length Bunk	8' 6-13/16"	8' 6-13/16"	8' 6-13/16"	8' 6-13/16"	8' 6-13/16"	8' 6"
Interior Width	97 5/8"	97 5/8"	97 5/8"	97 5/8"	97 5/8"	97 5/8"
Interior Height Main Floor	7' 6"	7' 6"	7'-6"	7' 6"	7'-6"	7' 6"
Interior Height Bunk	40"	40"	40"	40"	40"	40"
Minimum Ground Clearance ***	14 3/4"	9 3/4"	14 3/4"	9 3/4"	14 3/4"	9 3/4"
Rear Door Opening Width	90"	90"	90"	90"	90"	90"
Rear Door Opening Height	85"	85"	85"	85"	85"	85"
Width Between Wheel Wells	81"	81"	81"	81"	81"	81"
Brakes	4 Wheel Electric					
Tire Size	ST235/85R16/LRG	ST235/85R16/LRG	ST235/85R16/LRG	ST235/85R16/LRG	ST235/85R16/LRG	ST235/85R16/LRG
Hitch Height (Positions 1,2,3,4)	31 7/8", 34 1/2", 37 1/8", 39 3/4"	31 7/8", 34 1/2", 37 1/8", 39 3/4"	31 7/8", 34 1/2", 37 1/8", 39 3/4"	31 7/8", 34 1/2", 37 1/8", 39 3/4"	31 7/8", 34 1/2", 37 1/8", 39 3/4"	31 7/8", 34 1/2", 37 1/8", 39 3/4"
Hitch Type (GN - prepped for 5WH)	GN (5wh available)					
Hitch Ball Size	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"	2-5/16"
Landing Gear - Dual 12K	Manual	Hydraulic	Manual	Hydraulic	Manual	Hydraulic
Floor Crossmembers	16" OC					
Wall Studs	16" OC					
Ceiling Crossmembers	16" OC					

Notes

*Estimated Dry Weight

** Unloaded

*** To Bottom of Step