



PLA 350 14' Model

## KEY FEATURES + OPTIONS

- Full Perimeter Aluminum Frame with All-Tube Aluminum Construction (6-Sided, No Mechanical Fasteners)
- 1 Piece Aluminum Roof, Enclosed Underbelly with Radiant Barrier, Composite Ramp Door (No Wood)
- 270° 2 Tier Modular Track System & Generous In-Floor Tie-Down Features
- Durable Material Construction Throughout (No Wood-Hypo-Allergenic, Low Maintenance, Extended Life of Product)
- 360° R7 Closed Cell Insulation (Temperature & Sound Dampening)
- Torsion Axles, Exterior Modular Track System, Premium Aluminum Wheels

## SPECIFICATIONS

SIZES	Exterior Dimensions (L x W x H)	19' 2" x 8' 11" x 9' 4"	PKGS	Base Unit	15 Amp Shore
	Interior Dimensions (L x W x H)	14' x 6' 5" x 6' 4"		Base Package	30 Amp
	Ramp Door Opening (W x H)	76" x 75"		Wall Cabinets (Aluminum)	7 Varieties
	Ground Clearance Height	11 1/2"		Base Cabinets (Aluminum)	5 Varieties
WEIGHTS	Gross Vehicle Weight Rating (GVWR)	5,000 lbs	MODULES	Furniture/Tables	6 Varieties
	Estimated Curb Weight	1,400 lbs *		Doors/Drawers	4 Varieties
	Estimated Carry Capacity	3,600 lbs *		Power Collection/Storage	7 Varieties
	Estimated Hitch Weight	250 lbs *		Portable Appliances	8 Solutions
AXLE TIRE	2" Coupler	5,00 lbs	AMENITIES	Portable Media	3 Solutions
	Axle Size	1 x 5,200 lbs		In-Floor Storage	2.6 cu ft
	Tire Size	225/75R15D			

## WHAT CAN TOW THIS?



### COMPACT TRUCK/ MID-SIZE SUV

GVWR **5,000 lbs**  
 Estimated Curb Weight **1,400 lbs \***  
 Estimated Carry Capacity **3,600 lbs \***  
 (\* Before Modules, When Properly Equipped)



SCAN FOR  
FULL DETAILS